

Fluidum PC165

Mid to High-Range PCE Based Concrete Superplasticizer
Comply to ASTM C494 Type A and F, and BS EN 934-2

DESCRIPTION

Fluidum PC165 a Mid to high efficiency liquid fourth generation superplasticizer based on selected Polycarboxylate ether polymers. **Fluidum PC165** has been designed to impart exceptional rheological properties to fresh concrete. It improves considerably the placing and finishing of concretes and enhances the ease of concrete pumping for all construction activities. **Fluidum PC165** is recommended to produce pumpable concrete requiring low viscosity, long workability retention and high compressive strength

TYPICAL PROPERTIES

Appearance: : Brownish Liquid.
Specific Gravity: 1.055 ± 0.02 at 25 ± 2°C.
Chloride Content: Nil according to BS 5075.

COMPATIBILITY

With Cements:

Fluidum PC165 can be used with most types of Portland cements as well as Pozzolanic Cements, Natural Pozzolan, Ground Granulated Blast Furnace Slag (GGBFS) (**Arcrete BFS100**), Micro Silica (**Arcrete MS920**) and Fly Ash (**Arcrete FA10**). For use with other special cements, we recommend you contact Arkaz Technical Department.

With Other Admixtures:

Fluidum PC165 performance will be affected by the presence of other chemical admixtures, we advise that all admixtures be added separately into the mix.

We recommend Arkaz be contacted for Advice in these circumstances.

ADDITION RATES

Range:

0.5%-3% (v/w) by wt. of cement

As with most products of this type the magnitude of the effect obtained with **Fluidum PC165**, is governed by the quantity of product used, W/C ratio, and the specific nature of the concrete and constituent materials.

It is necessary therefore to assess performance under site conditions using actual materials to determine optimum performance and dosage.

For advice and assistance with trials we recommend that you contact Arkaz.

EFFECTS OF OVERDOSING

The effects of overdosing **Fluidum PC165** are a function of the degree of overdose. When concrete has been produced, which has been overdosed, the level of workability will increase and may under certain situations lead to segregation of the mix. Setting time may also increase, especially if the overdosed concrete is subjected to low ambient temperatures, or if sulfate resisting or certain pozzolanic cements are employed.

DISPENSING

It is preferable that **Fluidum PC165** should be introduced into the mixer by means of independent automatic dispensing equipment. Such equipment or advice on dispensing can be obtained from Arkaz.

METHOD OF USE

Fluidum PC165 is supplied ready for use. It should be added to concrete mixes either during the mixing cycle or at the same time as the water, or alternatively it should be added in its supplied form to a normal concrete mix a few minutes before the pour is made. In the latter case, further mixing should be provided to ensure complete dispersion.

PACKAGING

Fluidum PC165 is supplied in 210 non-returnable drums. Alternatively, 1,000-liter totes and bulk deliveries can be arranged.

HEALTH AND SAFETY

For further information, please Check Product Material Safety Data Sheet or consult Arkaz Technical Department.

STORAGE & SHELF LIFE

Fluidum PC165 should be stored in original containers or suitable closed tanks preferably away from extremes of temperature. The product should always be kept in shaded storage.

Storage Life in Manufacturer's Drums:
12 months from date of manufacture.

Storage Life in Bulk Storage:
12 months from date of delivery.

TECHNICAL SERVICE

The technical service department of Arkaz is available to assist in the correct and best use of our products, these resources and advice are at your disposal entirely without obligation.

Please contact:
concretedoctor@arkaz.com

LEGAL DISCLAIMER

The information given is based on data and knowledge considered to be true and accurate and is offered for the user's consideration, investigation and verification. Since the conditions of use are beyond our control, we do not warrant the results to be obtained. Please read all statements, recommendations or suggestions in conjunction with our conditions of sale including those limiting warranties and remedies which apply to all goods supplied by us. No statement, recommendation or suggestion is intended for any use which would violate or infringe statutory obligations or any rights belonging to a third party.

These products may be covered by patents or patents pending.



Copyright 2021
Printed in K.S.A. Version 2.0
4-March-2021