

Fluidum PC755



High Efficiency Liquid Superplasticizer for concrete combining both enhanced consistence Retention and Rheology performance

DESCRIPTION

Fluidum PC755 is a high efficiency liquid fourth generation superplasticizer based on selected Polycarboxylate ether polymers **Fluidum PC 755** has been designed to impart exceptional rheological properties to fresh concrete It improves considerably the placing and finishing of concretes and enhances the ease of concrete pumping for all construction activities **Fluidum PC 755** is recommended to produce pumpable concrete requiring low viscosity, long workability retention and high compressive strength.

TYPICAL PROPERTIES

| | |
|----------------------------------|---------------------------|
| Appearance: | Brownish viscous Liquid |
| Specific Gravity: | 1.055 ± 0.02 at 25°C |
| Chloride Content: | Nil according to BS 5075. |
| ASTM C494 classification: | Type F |

COMPATIBILITY

With Cements:

Fluidum PC755 can be used with all types of Portland cements as well as Pozzolanic Cements, Ground Granulated Blast Furnace Slag (GGBFS), Micro Silica and Fly Ash. For use with other special cements or SCM, we recommend you contact Arkaz Technical Service Department

With Other Admixtures:

Fluidum PC755 performance will be affected by the presence of other chemical admixtures, we advise that all admixtures be added separately into the mix.

We recommend that all admixtures be added separately into the mixer

ADDITION RATES

Range:

100 ml - 3000 ml per 100 kg cement
0.1% – 3 % (v/w) by wt. of cement

As with most products of this type of the magnitude of the effect obtained with **Fluidum PC755**, is governed by the quantity of product used, w/c ratio, and the specific nature of the concrete and constituent materials.

It is necessary therefore to assess performance under site conditions using actual materials to determine optimum performance and dosage

For advice and assistance with trials we recommend that you contact Arkaz.

EFFECTS OF OVERDOSING

The effects of overdosing **Fluidum PC755** are a function of the degree of overdose. When concrete has been produced, which has been overdosed, the level of workability will increase and may under certain situations lead to segregation of the mix. Setting time may also increase, especially if the overdosed concrete is subjected to low ambient temperatures, or if sulfate resisting or certain pozzolanic cements are employed.

DISPENSING

It is preferable that **Fluidum PC755** should be introduced into the mixer by means of independent automatic dispensing equipment. Such equipment or advice on dispensing can be obtained from Arkaz.

METHOD OF USE

Fluidum PC755 is supplied ready for use. When producing high workability concrete or concrete of low W/C ratio it is recommended that **Fluidum PC755** be added in its supplied form to the batching water prior to addition of the cementitious component.

Addition of any other chemical admixture should be undertaken separately.

PACKAGING

Fluidum PC755 is supplied in 210 non-returnable drums. Alternatively, 1,000-liter totes and bulk deliveries can be arranged.

HEALTH AND SAFETY

For more safety information you can check the MSDS or contact Arkaz technical department.

STORAGE & SHELF LIFE

Fluidum PC755 should preferably be stored away from extremes of cold or heat. Always keep product in shaded storage.

Storage Life in Manufacturer's Drums:
12 months from date of manufacture.

Storage Life in Bulk Storage:
12 months from date of delivery.

TECHNICAL SERVICE

The technical service department of Arkaz is available to assist in the correct and best use of our products, these resources and advice are at your disposal entirely without obligation. Please contact us via our website arkaz.com

LEGAL DISCLAIMER

The information given is based on data and knowledge considered to be true and accurate and is offered for the user's consideration and verification. Since the conditions of use are beyond our control, we do not warrant the results to be obtained. Please read all statements, recommendations or suggestions in conjunction with our conditions of sale including those limiting warranties and remedies which apply to all goods supplied by us. No statement, recommendation or suggestion is intended for any use which would violate or infringe statutory obligations or any rights belonging to a third party.

These products may be covered by patents or patents pending.