

Fluidum R7500

High-Range Water Reducing Concrete Admixture for Hot Weather Readymix Concrete Applications
ASTM C494 Type F & G and BS EN 934-2

DESCRIPTION

Fluidum R7500 is a High-Range Water Reducer developed to enhance and improve the slump retaining properties of concrete, whilst providing improved ultimate compressive strengths. It can be used at a range of dosage levels to:

- Reduce water content
- Reduce Cement Content
- Increase compressive strength
- Increase workability

Fluidum R7500 a high efficiency liquid superplasticizer which has been designed to impart exceptional rheological properties to fresh concrete. It improves considerably the placing and finishing of concretes and enhances the ease of concrete pumping for all construction activities. It is based on modified synthetic carboxylates polymers, **Fluidum R7500** is recommended to produce concrete requiring low viscosity, long workability retention and high compressive strength. The product is especially beneficial in either high strength or high durability concrete mix designs in hot climatic conditions.

TYPICAL PROPERTIES

Appearance: Brown Liquid

Specific Gravity: 1.060 ± 0.02 at 25 ± 2°C

Air Entrainment: 1.0 % Max from Control Mix.

Chloride Content: Nil, according to BS5075.

EFFECTS OF OVERDOSING

Serious overdosing of **Fluidum R7500** will generally produce a concrete mix of even greater workability, set retardation and a slight increase in air entrainment may be noticed. In SRC mixes and in cooler weather, set retardation will be further increased.

COMPATIBILITY

With Cements:

Fluidum R7500 can be used with most types of Portland cements as well as Pozzolanic Cements, Natural Pozzolan, Ground Granulated Blast Furnace Slag (GGBFS) (**Arcrete BFS100**), Micro Silica (**Arcrete MS920**) and Fly Ash (**Arcrete FA10**). For use with other special cements, we recommend you contact Arkaz Technical Department.

With Other Admixtures:

Fluidum R7500 performance will be affected by the presence of other chemical admixtures. We recommend Arkaz Technical service Department to be contacted for Advice in these circumstances.

DISPENSING

It is preferable that **Fluidum R7500** should be introduced into the mixer by means of independent automatic dispensing equipment. Such equipment or advice on dispensing can be obtained from Arkaz Technical Service Department.

METHOD OF USE

Fluidum R7500 is supplied ready for use. It should be added to concrete mixes either during the mixing cycle or at the same time as the water, or alternatively, it should be added in its supplied form to a normal concrete mix a few minutes before the pour is made.

In the latter case further mixing should be provided to ensure complete dispersion.

ADDITION RATES

Range:

0.25% - 2.5 % (v/w) by wt. of cement
250 ml - 2500 ml per 100 kg cement

As with most products of this type the magnitude of the effect obtained with **Fluidum R7500**, is governed by the quantity of product used, water-cement ratio, and the specific nature of the concrete and constituent materials. It is necessary, therefore, to assess performance under site conditions using actual materials to determine optimum performance and dosage and effect on both plastic and hardened concrete properties such as cohesiveness, workability retention, setting characteristics, rate of early strength gains, ultimate strength and shrinkage where these are of importance.

PACKAGING

Fluidum R7500 is supplied in 210 non-returnable drums. Alternatively, 1,000-liter totes and bulk deliveries can be arranged.

HEALTH AND SAFETY

For more Safety information you can check Product Material Safety Data Sheet, send an email to ConcreteDoctor@arkaz.com or Contact Arkaz Technical Department.

STORAGE & SHELF LIFE

Fluidum R7500 should be stored in original containers or suitable closed tanks preferably away from extreme temperature. Always keep product in shaded storage.

Storage Life in Manufacturer's Drums: 12 months from date of manufacture.

Storage Life in Bulk Storage: 12 months from date of delivery.

TECHNICAL SERVICE

The technical service department of Arkaz is available to assist in the correct and best use of our products, these resources and advice are at your disposal entirely without obligation.
Please contact:
concretedoctor@arkaz.com

LEGAL DISCLAIMER

The information given is based on data and knowledge considered to be true and accurate and is offered for the user's consideration, investigation and verification. Since the conditions of use are beyond our control, we do not warrant the results to be obtained. Please read all statements, recommendations or suggestions in conjunction with our conditions of sale including those limiting warranties and remedies which apply to all goods supplied by us. No statement, recommendation or suggestion is intended for any use which would violate or infringe statutory obligations or any rights belonging to a third party.

These products may be covered by patents or patents pending.



Copyright 2023
Printed in K.S.A. Version 2.0
23-March-2021