



PMH-T-D80

Double-sided Tape

Product Description

PMH-T-D80 Double-sided tape is a specially formulated high performance double-sided pressure sensitive tape. It is designed for membrane terminations, detailings, patching of damaged membranes and penetrations.

Application Areas

The product can be used for membrane termination or repair works.

Typical Properties

| Item | Value |
|---------------------------|----------|
| Length | 50 m |
| Width | 80 mm |
| Thickness | 0.4 mm |
| Peel adhesion(ASTM D1876) | 0.8 N/mm |

Packing Specifications

| Item | Description |
|---------------|--|
| Packing | 12 rolls per box |
| Specification | 80mm (W) x 50m (L) x 0.4mm (Thickness) |

Transportation and Storage

- Stored in well-ventilated and dry places
Storage temperature shall be below 45 °C .
- Stay away from direct sunlight, rain and high temperature.
- Avoid contact with acids, alkalis, oils and organic solvents.

PMH-T-D80

Double-sided Tape

Precautions

- It is not recommended to use the tape when temperature is lower than 5°C as bonding strength of the tape may be affected. The temperature shall be maintained for 24 hours after the tape is installed.
- Make sure that substrate is clean & dry before using the tape. When applying tape on the membrane, the lapped areas shall be pressed hard to ensure a good bonding effect.
- Please read the MSDS carefully, our experts will be pleased to give you advice about safety, health and environmental issues.

Product Liability

The above information and suggestions are based on our experience and are for reference only. Since Oriental Yuhong Company and its dealers cannot control the storage and handling conditions after delivery, Oriental Yuhong shall not be liable for any quality issues caused by improper use. No technical information shall be provided to any third parties without manufacturer's consent.