

ARKPROOF WP80

Hydrophobic Integral Waterproofing Concrete Admixture

DESCRIPTION

ARKPROOF WP80 is a chloride free organic admixture and supplied as a brown liquid. It reacts with the cement hydration process byproducts to form a hydrophobic ingredient to reduce the capillary suction and prevent the absorption of potentially damaging soluble material, resulting in concrete with enhanced durability. The water insoluble organic Material in **ARKPROOF WP80** acts as a non-wettable lining on the walls of all pores and voids in the mix, making them water repellent, making concrete more resistant against Carbonation and Efflorescence.

TYPICAL PROPERTIES

Appearance: Brown Liquid
Specific Gravity: 1.04 at 25°C
Air Entrainment: 2% Max from control mix.
Chloride Content: Nil as per BS 5075

COMPATIBILITY

With Cements:

ARKPROOF WP80 can be used with most types of Portland cements as well as Pozzolanic Cements, Ground Granulated Blast Furnace Slag (GGBFS), Micro Silica and Fly Ash.

With Other Admixtures:

ARKPROOF WP80 is compatible with other ARKAZ admixtures in the same concrete mix. All admixtures should be added to the concrete separately and must not be mixed together prior to addition. The performance of concrete containing more than one admixture should be assessed by trial mixes to ensure the desired combination of effects is obtained.

ADDITION RATES

Processing & Dosage:

Processing of undiluted product as a water resisting admixture according to EN 934-2:2009 Tab. 9. The recommended admixture range is 1 % to 2.5 % of the cement content. Dosage different than that mentioned can be used as per Concrete Mix design specifications.

ARKPROOF WP80 is added either simultaneously with or immediately after the mixing water.

ARKPROOF WP80 water absorption @7 days \leq 1 % As per BS 1881: Part122.

If **ARKPROOF WP80** is used in the new built concrete structure, it will lengthen its life and maintain its appearance as it contains Chemicals that make the concrete watertight.

DISPENSING

It is preferable that **ARKPROOF WP80** should be introduced into the mixer by means of independent automatic dispensing equipment. Such equipment or advice on dispensing can be obtained from Arkaz.

METHOD OF USE

ARKPROOF WP80 is supplied ready for use. It should be added to concrete mixes either during the mixing cycle or at the same time as the water, or alternatively it should be added in its supplied form to a normal concrete mix a few minutes before the pour is made. In the latter case further mixing should be provided to ensure complete dispersion.

PACKAGING

ARKPROOF WP80 is supplied in 210 non-returnable drums. Alternatively, 1,000-liter totes and bulk deliveries can be arranged.

HEALTH AND SAFETY

For more Safety information you can check Product Material Safety Data Sheet, send an email to ConcreteDoctor@arkaz.com or Contact Arkaz Technical Department.

STORAGE & SHELF LIFE

ARKPROOF WP80 should be stored in original containers or suitable closed tanks preferably away from extreme temperature. Always keep product in shaded storage.

Storage Life: 12 months provided the temperature is kept within the range of 2°C to 30°C. Freezing point: Approximately -2°C.

TECHNICAL SERVICE

The technical service department of Arkaz is available to assist in the correct and best use of our products, these resources and advice are at your disposal entirely without obligation.

Please contact:
concretedoctor@arkaz.com

LEGAL DISCLAIMER

The information given is based on data and knowledge considered to be true and accurate and is offered for the user's consideration, investigation and verification. Since the conditions of use are beyond our control, we do not warrant the results to be obtained. Please read all statements, recommendations or suggestions in conjunction with our conditions of sale including those limiting warranties and remedies which apply to all goods supplied by us. No statement, recommendation or suggestion is intended for any use which would violate or infringe statutory obligations or any rights belonging to a third party.

These products may be covered by patents or patents pending.



Copyright 2021
Printed in K.S.A. Version 2.0
21-March-2021